



Castrol Garden 2T

Cleaner spark plugs

Description

Castrol Garden 2T is an advanced high quality 2-stroke engine oil specially designed to give good anti-wear and anti-seizure properties for use in lawn mowers, chain saws and other garden machinery.

Application

Castrol Garden 2T is suitable for all 2T garden equipment and for use in pre-mix and oil injection systems with both leaded and unleaded petrol and for fuel/oil mixture ratios, as recommended by the engine manufacturer of up to 1:50 / 2%.

Advantages

- Good anti-wear and anti-seizure properties.
- Protection from build up of carbon deposits.
- Prevention from spark plug fouling.

Typical Characteristics

Name	Method	Units	Typical
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	12.7
Density @ 15C, Relative	ASTM D4052	g/ml	0.8773
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	56
Pour Point	ASTM D97	°C	-27
Total Base Number, TBN	ASTM D2896	mg KOH/g	1.52

Product Performance Claims

API TC

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Garden 2T

04 Sep 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

Orders/Enquiries: 0345 6008125 Technical Enquiries: 0345 082 1719 BP (Ireland) Ireland Orders/Enquiries: 1850 930 3942 Ireland Technical Enquiries: 1800 509 353

www.castrol.com/uk