



Castrol MAGNATEC STOP-START 5W-30 C3

NON-STOP PROTECTION AND IMPROVED FUEL ECONOMY FROM EVERY START

Description

Busy driving, reinvented.

All cars, even those with the latest stop-start engine technology don't perform at their best in traffic congestion. And congestion has dramatically increased over the past 10 years, causing engine wear and wasting fuel.

That's why we created new Castrol MAGNATEC STOP-START, combining DUALOCK molecule technology with Castrol's most efficient full synthetic base oils.

- Forms a powerful force-field of wear protection
- Dramatically reduces both warm-up¹ and stop-start² wear by 50%
- Improved fuel economy³

Castrol MAGNATEC STOP-START 5W-30 C3 is tested in Hybrid*.

Non-stop protection from every start, even for vehicles with modern stop-start engine technology

¹ Tested versus the Sequence IVA API SN wear limit.

² Tested versus the CEC OM646LA ACEA wear limits.

³ Compared to an industry reference 15W-40 oil.

* Toyota Prius, EPA NYCC.

Application

Castrol MAGNATEC STOP-START 5W-30 C3 is suitable for use in automotive gasoline and diesel vehicles where the manufacturer recommends an ACEA C3, API SN 5W-30 lubricant.

Castrol MAGNATEC STOP-START 5W-30 C3 is approved for use in vehicles from leading manufacturers, please refer to your owner's handbook.

Typical Characteristics

Name	Method	Units	Castrol MAGNATEC Stop-Start 5W-30 C3
Density @ 15C, Relative	ASTM D4052	g/ml	0.853
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	12.1
Viscosity, CCS -30C (5W)	ASTM D5293	mPa.s (cP)	5800
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	72
Viscosity Index	ASTM D2270	None	165
Pour Point	ASTM D97	°C	-42
Flash Point, PMCC	ASTM D93	°C	201
Ash, Sulphated	ASTM D874	% wt	0.8

Product Performance Claims

ACEA C3

API SN

BMW Longlife-04

Meets Fiat 9.55535-S3

MB-Approval 226.5/ 229.31/ 229.51

Renault RN 0700 / RN 0710

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol MAGNATEC STOP-START 5W-30 C3

24 Mar 2023

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

Orders/Enquiries: 0345 6008125 Technical Enquiries: 0345 082 1719 BP (Ireland) Ireland Orders/Enquiries: 1850 930 3942 Ireland Technical Enquiries: 1800 509 353

www.castrol.com/uk