



### Typical Inspection Data:

Density @ 20°C	1.124 g/cm <sup>3</sup>
Appearance	Blue liquid
Boiling Point	168°C

### Protection Levels:

Super Coldmaster	Approx. Protection
33%	-18°C
50%	-36°C
60%	-52°C

## Super Coldmaster Concentrate

### Recommended by Comma for applications requiring:

- Conforms to: BS6580:2010; AFNOR NFR 15-601

### Product Features:

- A Mono Ethylene Glycol (MEG) based engine coolant / anti-freeze concentrate.
- Suitable for use in all types of vehicle requiring an MEG coolant.
- Suitable for Ferrous and Aluminium engines.
- 2 years full protection.
- Helps prevent winter freezing and summer boil over. Also improves heat transfer.
- NAP (Nitrite, Phosphate and Amine) free.

### Directions for use:

- Dilute with de-ionised water in accordance with the vehicle manufacturer's instructions.
- Pour into vehicle cooling system.
- Minor spills should be soaked up with absorbent granules, sand or dirt. The spillage site should then be washed with soapy water and dried.

### Handling:

- Remove spills from paintwork immediately.
- Keep away from foodstuffs and oxidising agents.
- Store in airtight container.
- Avoid galvanised containers for storage or dispensing as they will corrode and contaminate the product.

### Shelf Life:

- 3 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 24-06-2021

Moove Lubricants Ltd. Dering Way, Gravesend, Kent DA12 2QX, England.

Tel: +44 (0)1474 564 311, Fax: +44(0)1474 333 000 Email: sales@commaoil.com [www.CommaOil.com](http://www.CommaOil.com)