



## X-Flow Type FE 0W-30 Fully Synthetic

**Recommended by Comma for applications requiring:**

Ford WSS-M2C950-A;  
ACEA C2

### Product Features:

- Fully synthetic, mid SAPS 0W-30 oil for Ford petrol and diesel engines from 2014 onwards. Designed for high fuel efficiency.
- Designed for high fuel efficiency.
- Suitable for petrol and diesel vehicles.
- To ensure correct oil selection use Comma's latest application guide instore or online at [www.CommaOil.com](http://www.CommaOil.com).

### Typical Inspection Data:

Density @ 20°C	0.845 g/cm <sup>3</sup>
Viscosity @ 100°C	9.7 cSt
Viscosity @ 40°C	50 cSt
Viscosity Index	183
Viscosity CCS @ -35 °C	6100 cP
T.B.N.	8.0 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.11%
Calcium	0.19%
Phosphorus	0.09%
Colour	Brown
Flash Point	>200°C
Pour Point	-42°C

### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

### Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 15-12-2021